

SURFACE MOUNT SUPER FAST GLASS PASSIVATED RECTIFIERS


REVERSE VOLTAGE - **50** to **600** Volts
 FORWARD CURRENT - **3.0** Amperes

FEATURES

- Super fast switching time for high efficiency
- Low forward voltage drop and high current capability
- Low reverse leakage current
- Plastic material has UL flammability classification 94V-0

MECHANICAL DATA

- Case: Molded Plastic
- Polarity: Color band denotes cathode
- Weight: 0.003 ounces, 0.093 grams
- Mounting position: Any



Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60Hz, resistive or inductive load.

For capacitive load, derate current by 20%

CHARACTERISTICS	SYMBOL	ES3A	ES3B	ES3D	ES3G	ES3J	UNIT	
Maximum Recurrent Peak Reverse Voltage	V _{RRM}	50	100	200	400	600	V	
Maximum RMS Voltage	V _{RMS}	35	70	140	280	420	V	
Maximum DC Blocking Voltage	V _{DC}	50	100	200	400	600	V	
Maximum Average Forward Rectified Current @T _A =55 °C	I _(AV)	3.0					A	
Peak Forward Surge Current 8.3ms Single Half Sine-Wave Super Imposed on Rated Load(JEDEC Method)	I _{FSM}	125					A	
Peak Forward Voltage at 3.0A DC	V _F	0.95		1.3		1.7	V	
Maximum DC Reverse Current at Rated DC Blocking Voltage @T _J =25°C @T _J =100°C	I _R	5.0					100	μA
Maximum Reverse Recovery Time(Note 1)	T _{RR}	35					nS	
Typical Junction Capacitance (Note2)	C _J	70			45		pF	
Typical Thermal Resistance (Note3)	R _{θJA}	20					°C/W	
Operating Temperature Range	T _J	-55 to +150					°C	
Storage Temperature Range	T _{STG}	-55 to +150					°C	

NOTES: 1.Measured with I_F=0.5A, I_R=1A, I_{RR}=0.25A

2.Measured at 1.0 MHz and applied reverse voltage of 4.0V DC

3.Thermal resistance junction to ambient.

FIG. 1 – FORWARD CURRENT DERATING CURVE




FIG. 2 – MAXIMUM NON-REPETITIVE SURGE CURRENT




FIG.3 – TYPICAL JUNCTION CAPACITANCE




FIG.4-TYPICAL FORWARD CHARACTERISTICS

